

VEHICLE LIGHTS

HOME

PRODUCTS

#1 Contractor Light in America



HIGHLIGHTER™ - MINI-LIGHTBAR

Provides exceptional warning power in a compact package, ideal for a variety of applications where full-length lightbars are not practical. The Highlighter mini-lightbar is available in two mounting options; permanent or suction cup magnetic. The magnetic version comes with a 10-foot cord and cigarette plug adapter. Meets SAE J845 Class 1 requirements. 80,000 candelas per flash.

Dimensions: 15.8 in x 7 in x 5.3 in (LxWxH)
Voltage: 12/24 VDC
Flash Rate: 285-525/min.

12V Permanent #13804550 12V Magnetic #13804650

SENTRY®


The Sentry® rotating beacon is a reliable, effective warning light in an attractive, compact package. Sentry beacons combine a large parabolic reflector and a brilliant 55-watt halogen bulb to produce an attention getting 80,000 candelas per flash. Meets SAE J845 Class 1 requirements

Applications:

- Tow and Recover vehicles
- Utility trucks
- Construction vehicles
- Pickup trucks
- Landscaping vehicles

Dimensions: 6.4 in x 6.5 in
Voltage: 12V
Flash Rate: 95/min

Permanent #13811500
Magnetic #13811600



CADET

Compact, 3-7/8" high, rotating halogen beacon ideal for dash or deck. Includes 8' straight power cord with cigar plug and 50# pull magnet, light shield, and hook and loop fastener pad. Class II requirements. 14,000 candelas per flash.

Permanent/Magnetic mount.

#13804100

Applications:

- Tow and Recover vehicles
- Utility trucks
- Construction vehicles
- Pickup trucks
- Landscaping vehicles

Dimensions: 8.5 in x 7.5 in
Voltage: 12V
Flash Rate: 95/min



MODEL 100

The Model 100 rotating beacon is an economical, dependable warning light. Years of reliable service have made the Model 100 beacon an industry standard. Its sturdy design and effective warning capability make this light ideal for a variety of applications. Meets SAE J845 Class 1 requirements 80,000 candelas per flash.

Permanent #13811700

Magnetic #13811800



Related Links:

Construction Supplies
Arrow Boards
Changeable Message Signs

Intensity Vs Effective
Distance Halogen Rotating
Beacons

- 50-100 Yards
14,000-18,000 Candela
- 100-220 Yards
20,000-30,000 Candela
- 1/4 - 1/2 Mile
33,000- 40,000 candela
- 1/2 - 3/4 Mile
40,000-48,000 Candela
- 1 Mile +
50,000 Candela +

Candela:
A unit of Luminous intensity
from a steady on source.

VEHICLE LIGHTS

HOME

PRODUCTS



2012HPA

2000 SERIES STROBE BEACONS

- Fully enclosed base: Sturdy polycarbonate base or cast aluminum base, all strobe power supplies are encased within the base itself for added protection against moisture and vibration.
- Silicone coated power supplies: For added protection against the elements, all strobe power supplies are double dipped in a uniquely formulated silicone mixture before being secured into the base enclosure.



2012LPA

- | | |
|------------------------------|-----------|
| 2012LPA Permanent/Pipe Mount | #13801125 |
| 2012LPA Magnetic Mount | #13801325 |
| 2012HPA Permanent/Pipe Mount | #13801225 |
| 2012HPA Magnetic Mount | #13801425 |

Specifications:

- Class 2 SAE Certified
- Output power: 15 watts; 8 joules
- Flash rate: 120 single FPM
- 12/24 VDC
- Base Material: polycarbonate



2015LPA

Specifications:

- Class 2 SAE Certified
- Output power: 15 watts; 13 joules
- Flash rate: 72 QuintFlash per minute, includes multiple field selectable
- 12/24 VDC
- Manual Hi/Low intensity control
- Base Material: polycarbonate or aluminum base



2015HPA

- | | |
|------------------------------|-----------|
| 2015LPA Permanent/Pipe Mount | #13800125 |
| 2015LPA Magnetic Mount | #13800325 |
| 2015HPA Permanent/Pipe Mount | #13800225 |
| 2015HPA Magnetic Mount | #13800425 |

