
Pedestrian Crosswalk System

Solar-Powered BlinkerSign®





20W/44AH TOP-OF-POLE SELF-CONTAINED CONTROL CABINET			
Housing	NEMA 3R type aluminum		
Solar Panel	20 watt		
Battery	12V, up to 44Ah		
Battery Lifespan	3 to 5 years, field replaceable		
Mounting Options	Round Poles: 2 3/8" up to 4 1/2" ; Square posts: 1 3/4" up to 2 1/2"		
Mounting Hardware	Stainless steel hardware		
Warranty	3-year limited battery warranty 5-year limited battery warranty 10-year limited solar panel warranty		



Note: Specifications are approximate and subject to change. Some parts shown may be for illustration purposes only.

Pedestrian Crosswalk System

Solar-Powered BlinkerSign®



SUPPLY COMPANY

BLINKERSIGN®			
Sign Legend	W11-2, W11-15 and S1-1 options available		
Sign Substrate	.080" highway grade aluminum		
Reflective Sheeting	3M DG3 with anti-graffitit overlay		
Dimming	Variable based on photocell sensor input		
Flash Pattern	MUTCD sectioin 2A.07 compliant		
LED Type	Environmentally-sealed, high-power 1 watt		
LED Color	Amber		
LED Quantity	8		
LED Life Expectancy	100,000 hours		
Visibility	Daytime: more than 1,000 feet Nighttime: more than 1 mile		
Enclosed Channels	Protecting wiring against inclement weather, tampering and vandalism		
Mounting Brackets	Single post standard. Double post or Z-bar available		
Mounting Hardware	Various options available		
Wind Load Rating	Up to 90mph*		
Operating Temperature Range	-40°F to 122°F (-40°C to 50°C)		
Dimensions	24"W x 24"H x 1"D 30"W x 30"H x 1"D 36"W x 36"H x 1"D		
BLINKERBEAM® WIRELESS COMMUNICATION			
Frequency	900 MHz FHSS (Frequency Hopping Spread Spectrum)		
Range	90 feet (radio site survey recommended)		
Connectivity	Crosswalk and optional advanced warning LEDs activate concurrently		
ACTIVATIONS			
Push Button Activation		ADA push button, typical (<120 millisecond)	
User-Actuated Push Button		XAV2-LED or Bulldog 300, 20-second daily activations minimum	
Passive Detection		Wireless bollards	
Autonomy		23-day minimum	
BLINKERBEAM® WIRELESS			
BlinkLink	Optional cloud software with cellular modem**		



W11-2 BLINKERSIGN®



BLINKERBEAM®
WIRELESS RADIO







XAV2-LED PUSH BUTTON

BULLDOG PUSH BUTTON

Note: Specifications are approximate and subject to change. Some parts shown may be for illustration purposes only.